



**KING OIL, INC.**  
**KING L.P. GAS INC.**



## Maralube Moly

A lithium-base No. 2 grade grease fortified with polyethylene and molybdenum disulfide for extra protection against wear and water washout. A multi-purpose grease with proven performance in varied applications including automotive and commercial fleets, farm, construction, and industrial.

### Typical Properties of Greases

	<b>Moly</b>	<b>Maraplex EP2</b>	<b>Maratrac</b>	<b>Maratrac LT</b>	<b>Maratech HDP</b>
NLGI	2	2	2	1	2
Soap Type	Lithium	Lithium Complex	Lithium Complex	Lithium Complex	Polyurea
Performance Additives	EP Poly/Moly	EP Tackiness	EP/Moly Tackiness	EP Tackiness	EP
Texture	Smooth	Tacky	Tacky	Tacky	Smooth
Color	Gray	Red	Black	Black	Green
Dropping Point, °F	360	525	500	500	520
Penetration 60 Strokes	280	280	280	325	295
Viscosity of Extracted Oil					
cSt @ 40° C	154.9	195	460	120	350
cSt @ 100° C	14.8	20	30	12.0	27.5
Timken Load, Lbs.	45	60	50	50	60

*Serving you*

*24 hours a day, 7 days a week*

*We take it personally.*