



**KING OIL, INC.**  
**KING L.P. GAS INC.**



## Maratrac™ (#2 ) & Maratrac™ LT (#1)

### CONSTRUCTION & FARM GREASE WITH 3% MOLY DISULFIDE

Contains 3% moly disulfide to minimize wear under heavily loaded conditions.

#### IT PROVIDES:

- Heavy duty construction equipment, especially where high temperature or water contamination is a concern
- Low oil bleed
- Minimal separation for equipment requiring lubricant
- Stability during storage

#### APPLICATIONS INCLUDE:

- Ball joints and any points needing grease lubrication on bulldozers, scrapers, loaders, log skidders, and other heavy duty off-road equipment
- Farm tractors and implements

#### PERFORMANCE:

- Caterpillar MPGM, Case MPGM, John Deere, FMC, International Harvester, and Mack FG-C

### Typical Properties of Greases

	Moly	Maraplex EP2	Maratrac	Maratrac LT	Maratech HDP
NLGI	2	2	2	1	2
Soap Type	Lithium	Lithium Complex	Lithium Complex	Lithium Complex	Polyurea
Performance Additives	EP Poly/Moly	EP Tackiness	EP/Moly Tackiness	EP Tackiness	EP
Texture	Smooth	Tacky	Tacky	Tacky	Smooth
Color	Gray	Red	Black	Black	Green
Dropping Point, °F	360	525	500	500	520
Penetration 60 Strokes	280	280	280	325	295
Viscosity of Extracted Oil					
cSt @ 40° C	154.9	195	460	120	350
cSt @ 100° C	14.8	20	30	12.0	27.5
Timken Load, Lbs.	45	60	50	50	60