



KING OIL, INC.
KING L.P. GAS INC.



Super Maraplex EP-2

A red colored, lithium-complex, No. 2 grade grease fortified with an EP additive to prevent wear. Resists water and breakdown under operating temperatures as high as 400° F. Exhibits a tacky consistency to resist throw-off.

IT PROVIDES:

- Automotive use as well as farm and construction equipment and industrial applications
- Ideal for use in wheelbearings

PERFORMANCE:

- Meets NLGI grease classifications GC-LB for wheel bearing and chassis lubrication

Typical Properties of Greases

	Moly	Maraplex EP2	Maratrac	Maratrac LT	Maratech HDP
NLGI	2	2	2	1	2
Soap Type	Lithium	Lithium Complex	Lithium Complex	Lithium Complex	Polyurea Complex
Performance Additives	EP Poly/Moly	EP Tackiness	EP/Moly Tackiness	EP Tackiness	EP
Texture	Smooth	Tacky	Tacky	Tacky	Smooth
Color	Gray	Red	Black	Black	Green
Dropping Point, °F	360	525	500	500	520
Penetration 60 Strokes	280	280	280	325	295
Viscosity of Extracted Oil					
cSt @ 40° C	154.9	195	460	120	350
cSt @ 100° C	14.8	20	30	12.0	27.5
Timken Load, Lbs.	45	60	50	50	60