



KING OIL, INC.
KING L.P. GAS INC.



Premium AW II Hydraulic Oils

MARATHON PREMIUM AW II HYDRAULIC OIL

Oil formulated with high quality API Group II base-stocks and an additive package.

IT PROVIDES:

- It protects against:
 - Rust, oxidation, corrosion, foaming and wear

APPLICATIONS INCLUDE:

- Vane, gear, screw and radial pumps.
- Air compressors, circulating systems and enclosed gear cases

PERFORMANCE:

Meets or exceeds following requirements:

- Vickers I-286-S, M-2950-S
- Vickers 35VQ25
- Denison HF-1, HF-2, HF-0
- Denison TE6-C
- Din 51524, Part II
- CETOP RP91H
- U.S. Steel 136, 127
- Lee-Norse 100-1
- Jeffrey No. 87
- Afnor E 48-603(HM)
- B. F. Goodrich 0152
- Toshiba Machinery
- Racine, variable volume pump
- ASLE 64-1 TO 64-4, 70-1 TO 70-3
- Cincinnati Milacron P-68, P-69, P-70
- General Motors LH-04-1, LH-06-1, LH-15-
- Military Specifications 2075-T-H, 2110-T-H, 2135-T-H

Typical Properties

Grade	32	46	68	100
Color	0.5	0.5	0.51	.5
Viscosity,				
cSt @ 40° C	32.0	45.0	68.0	100.0
cSt @ 100° C	5.4	6.7	8.7	11.1
Viscosity Index	102	101	99	96
Pour Point, °F	-35	-35	-30	-20
Flash Point, °F	457	457	460	460

Serving you
24 hours a day, 7 days a week
We take it personally.